


Radio interference suppression filters

2-Lines 2-Stages

Type NFK14-8S22



CE - conform

Technical Data

Electrical data

Rated voltage U_R	see table below
Frequency	see table below
Rated current I_R	see table below
Overload current	$1,5 \times I_R$ $t < 2$ Min. 3 x / h
Inductance L_R	see table below
Capacity C_R	see table below
Derivation current	$< 0,75$ mA at 230V~, 50Hz
Discharge resistor	ca. 1M

Operating data

Duty circle	100%
Operating temperature range	-30°C to +80°C
Derating	-
Storage temperature range	-30°C...+105°C
Cooling	self cooling
	recommended respective distance 15mm each

Safety devices

Fuse for input	-
Fuse for output	-
Overload protection	-
MTBF	> 380.000 h

Safety data

Test voltage	2,5kV- (Conductor - PE)
Protection class	Class 2 (EN 60950)
Extra low safety potential	-
Ambient humidity	95% relative humidity, yearly average dewing allowed for use in tropical ambient
Protective class enclosure	IP 65
Protective class terminals	IP 20 (VGB4)
Vibration proof	> 30 g at 33Hz in X,Y and Z, acc. to IEC 60068-2-27

Applied construction regulations

according to VDE	VDE 0100, 0110, 0113, 0551, 0160/W2, 0806
IEC	IEC 60939-1, IEC 60939-2, IEC 60068-2-3 IEC 60068-2-11-52, IEC 60529, IEC 380
EN	EN 133200, EN 60068-1 EN 61000-6-1-2-3-4, EN 50178 EN 55011, EN 50204, EN 61558-2-17 EN 60204, EN 60529, EN 61000-4-2-3-4-5-6-8-11 EN 60068-1, EN 60068-2-1-2-3-6-27-30 EN 45501, EN 50021
CSA / UL	CSA-C 22.2 / UL 1283, UL 94V1

Mechanics

Mounting	On rails acc. to DIN 46277
----------	----------------------------

- ☐ High insertion loss over a broad frequency range
- ☐ Optimised against interferences in the lower frequency response
- ☐ 2-Stage design in order to improve the filtereffect
- ☐ Self-extinguishing polycarbonat housing in acc. to UL94V1
- ☐ Suitable for the tropics - Epoxy resin casted
- ☐ Safety acc. to VDE, EN, UL, CSA

Type	NFK14-8S22
Rated voltage	250VAC
Frequency	50 - 60Hz
Rated current	8,0Amp. at 40°C
Inductance	L1 2x2,7mH L2 2x170μH
Capacity	3 x 0,47μF(X2) 4 x 4700pF(Y2)
Dimensions (W x H x D)	45x75x110
Weight	approx. 0,70kg
Order-No.	51027

Insertion loss at 50

